Docket No.: 42P10307D

AMENDMENTS TO THE CLAIMS

Listing of claims:

1. (Withdrawn): A method of coupling a photonic component with a waveguide comprising:

positioning the photonic component against the waveguide; and aligning the photonic component with markings that have been lithographically-placed on a surface of the waveguide.

- 2. (Withdrawn): The method of claim 1, wherein the photonic component is a fiber optic bundle.
- 3. (Withdrawn): The method of claim 2 further comprising: aligning outermost optical fibers of the fiber optic bundle with the markings on the surface of the waveguide.
 - 4. (Withdrawn): The method of claim 3 further comprising: bonding the fiber optic bundle to the waveguide.
- 5. (Withdrawn): The method of claim 1, wherein the photonic component is a second waveguide.
- 6. (Withdrawn): A method of aligning a fiber optic bundle with a waveguide comprising:

using a lithographic process to place a marking on a surface of the waveguide, the marking indicative of an optical channel within the waveguide;

positioning the fiber optic bundle against the waveguide based on the marking; and

adjusting the fiber optic bundle until alignment is achieved.

Docket No.: 42P10307D Appl. No.: 10/672,329

4

Docket No.: 42P10307D

7. (Withdrawn): The method of claim 6 further comprising:

using the lithographic process to place a second marking on the surface of the waveguide, the second marking indicative of a second optical channel within the waveguide, wherein the positioning of the fiber optic bundle against the waveguide is also based on the second marking.

- 8. (Withdrawn): The method of claim 7, wherein the lithographic process uses an etch to place the first and second markings.
- 9. (Withdrawn): The method of claim 7, wherein the lithographic process uses an ink to place the first and second markings.
- 10. (Withdrawn): The method of claim 7, wherein the lithographic process deposits a layer of material that is distinguishable by the human eye to place the first and second markings.
- 11. (Withdrawn): The method of claim 7, wherein the marking is directly above the optical channel.
- 12. (Withdrawn): The method of claim 7, wherein the marking is lateral to the optical channel.
- 13. (Withdrawn): The method of claim 7, wherein the positioning of the fiber optic bundle against the waveguide is also based on alignment markings on the fiber optic bundle.
 - 14. (Withdrawn): The method of claim 13 further comprising: applying an epoxy between the fiber optic bundle and the waveguide.
 - 15. (Currently amended): A waveguide comprising: a first optical channel within the waveguide; and

Docket No.: 42P10307D Appl. No.: 10/672,329

5

Docket No.: 42P10307D

a first lithographically-defined marking on a surface of the waveguide indicative of the first optical channel within the waveguide;

wherein the first lithographically-defined marking is operative to assist in insertion of an optical fiber within the first optical channel.

- 16. (Currently amended): The waveguide of claim 15 further comprising:
- a second optical channel within the waveguide; and
- a second lithographically-defined marking on the surface of the waveguide indicative of the second optical channel within the waveguide;

wherein the second lithographically-defined marking is operative to assist in insertion of an optical fiber within the second optical channel.

- 17. (Original): The waveguide of claim 16, wherein the first lithographically defined marking and the second lithographically-defined marking are directly above the first optical channel and the second optical channel, respectively.
- 18. (Original): The waveguide of claim 17, wherein the first lithographically-defined marking and the second lithographically-defined marking are at an edge of the waveguide.
- 19. (Original): The waveguide of claim 18, wherein the waveguide comprises glass.
- 20. (Original): The waveguide of claim 18, wherein the waveguide comprises silicon.
- 21. (Original): The waveguide of claim 18, wherein the first optical channel and the second optical channel are on opposite sides of the waveguide.

Docket No.: 42P10307D Appl. No.: 10/672,329